

PAX IM25 UNATTENDED

Android smart POS info



SPECIFICATION AND FUNCTIONS

	Operating System	PayDroid Powered by Android 10
	Processor	Quad-core ARM Cortex-A53
	Memory	8GB Flash + 2GB LPDDR4 RAM
	Card Readers	Contactless
	Code Reader	Reads 1D & 2D Codes
	Display	3.5" TFT 480 x 320 (IM25 Standard and IM25 Flush EVA) 4.0" TFT 480 x 800 (IM25 Flush Kiosk)
	Comms Configurations	LAN + WiFi + Bluetooth LAN + WiFi + Bluetooth + 4G
	SIM/SAM	2 SAM 1 SIM (Optional)
	Keys / Buttons	1 x Reset key
	Audio	1 Speaker
	Ports	1 x USB Host 1 x USB Device 1 x LAN 1 x RS232 1 x Digital I/O 1 x MDB or 1x JVMA
	Physical	108 x 75 x 43mm Cutout: EVA CDM cutout 73 x 61mm (IM25 Standard) 92 x 141 x 43mm Cutout: OPP-C60 cutout 82 x 180mm (IM25 Flush Kiosk) 100 x 132 x 43mm Cutout: EVA SDM cutout 85 x 107mm (IM25 Flush EVA)
	Accessories	Mounting Fixture External 4G Antenna (Optional)
	Power Supply	7V-48V DC via MDB or RS232 or Digital I/O 24V DC via JVMA
	Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 6.x, SRED EMV Contactless L1 qPBOC L1 qUICS L2 Mastercard payPass L2 Visa payWave L2 American Express ExpressPay L2 Discover D-PAS L2 Interac_Flash L2 J/Speedy L2 Mastercard TQM FCC IC UL RoHS CE CSEC UKCC IP65 IK09 Felica VCCI 技适



OS
Powered by
Android

**PCI 6
SRED**

**Advanced
Connectivity**

**2 MP
Front**

**IP65
IK09**